

# Humminbird Helix 5 DI G2 DualBeam Plus Fishfinder



Humminbird



Product number: 410200-1

Humminbird Helix 5 DI G2 DualBeam Plus Sonar Fishfinder

449,00 €

410,99 €\* 410,99 €

HELIX 5 DI G2 | HELIX 5 Series | 410200-1

??The HELIX 5 DI G2 with our new user interface and operating system, features a brilliant 800H x 480V, 5" 256 color display with backlight. Down Imaging and DualBeam PLUS sonar with 4000 watts PTP power output. Maximize your angling experience with the Humminbird HELIX 5 DI fishfinder system.

## SPECS

- Display Size - Diagonal:5"
- Display Pixel Matrix:800H X 480V
- Display Type:Color TFT
- Display Colors Grayscale:16-bit
- Sonar Standard:Down Imaging/DualBeam PLUS
- Standard Sonar Coverage:16°, 28°, 45° & 75° @ -10db
- Standard Sonar Frequency:200/455/800 kHz
- Sonar Optional:None
- Target Separation:2.5"
- Power Output RMS:500 Watts
- Power Output Peak to Peak:4000 Watts
- Depth Capability:350 ft (DI) & 600 ft (2D)
- Temperature:Built-In Transducer
- Speed:Optional
- Backlight:LED
- Unit Size - Gimbal Mount:7.55"W x 4.64"H x 3.3"D

- Mount A Type:Gimbal Mount
- Unit Size - Indash Mount:7.55"W x 4.28"D x 1.13"D
- Mount B Unit Size2:Optional In-Dash
- Mounting Options:Gimbal or Optional In-Dash
- Transducer Standard:XNT 9 DI T
- Transducer Mounting:Transom
- Power Input:10.8-20 VDC
- Power Draw:650 mA

### **Equal to Helix 5 Sonar, but**

- Down Imaging 45° & 75°
- DualBeam Plus, 16° & 28° Sonar Coverage
- Depth Capability: 180m, and 100m (DI)
- Transducer XNT-9-DI-T

### **Supplies**

- Console
- Control Head
- Voltage Cable
- Operations Manual
- Transducer XNT-9-DI-T

\* incl. tax, plus [shipping](#)